

Gvision LCD Monitor J2ES-DA-WO

10.4" SVGA Display for high-end applications

- Product Specifications -

| Configuration | | J2ES-DA-WO |
|-----------------------------|--------------|--|
| LCD Display | | 12.1" TFT active matrix panel |
| Display Size (HxV mm) | | 246 x 184.5 |
| Pixel Pitch (HxV mm) | | 0.3075 x 0.3075 |
| Max. Resolution | | SVGA 800x600 |
| Contrast Ratio | | 100:1 (typical) |
| Brightness | | 200 cd/m ² (typical) |
| Response Time | | 30 ms (typical) |
| Display Color | | 262K |
| Viewing Angle | L/R | +40°~-40° (typical) |
| | U/D | +20°~-10° (typical) |
| PC Interface | Video | RGB analog 0.7Vpeak to peak |
| | Sync. | TTL positive or negative |
| Display Mode | | VGA 640X350 (70/85 Hz) |
| | | VGA 720X400 (70/85Hz) |
| | | VGA 640X480 (60/72/75/85 Hz) |
| | | SVGA 800x600 (56/60/72/75/85 Hz) |
| | | Mac. 832 x 624 (75Hz) |
| Signal Connector | | D-sub 15 pin |
| Front Control | | Power on/off with LED, Menu, Select, Adjustment (Up, Down) |
| OSD | | Brightness, Contrast, R.G.B. Contrast, Auto Setup, Frequency, Phase, H-position, V-position, Track, Text/Graphics, Expansion, Display Mode/Freq., Recall |
| Plug & Play | | DDC1/2B compatible |
| Power | Form | AC/DC Adapter |
| | Input/Output | Input AC 90-264V, 50-60Hz; Output DC 12V/3.5A |
| Operating Conditions | Temperature | 5°C~40°C (32°F~104°F) |
| | Humidity | 10%-80% (no condensation) |
| | Altitude | To 10,000 feet |
| Storage Conditions | Temperature | -20°C~60°C (-4°F~140°F) |
| | Humidity | 10%-80% (no condensation) |
| Dimensions (HxDxW inches) | | 9.3 x 12.3 x 2.9 |
| Weight (lbs) | | 6.6 |
| Standard Features & Options | Touch Panel | Touch-ready monitor engineered for easy touch screen installation. |
| | Video-In | S & RCA connectors |
| | Stand/Arm | Desktop stand, Photo frame stand, Adjustable arm |
| Certification | | C-UL, FCC, CE |

* Specifications are subject to change without notice.

Catch the wave of the future - Now!

Gvision USA Inc.

1582 Parkway Loop, Suite C, Tustin, CA 92780

