

LCD Monitor L4BX Series

MODEL: L4BX - 14.1" TFT DISPLAY

- Product Specification -

Configuration		L4BX
LCD Display		14.1" TFT active matrix panel
Display Size		285.7(H)x214.3(V) mm
Pixel Pitch		0.279(H)x0.279(V) mm
Max. Resolution		XGA 1024x768
Contrast Ratio		250:1 (typical)
Brightness		200 cd/m ² (typical)
Response Time		50 ms
Display Color		16M
Viewing Angle	L/R	+60°~-60° (typical)
	U/D	+70°~-30° (typical)
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/72/75/85 Hz)
		SVGA 800x600 (56/60/72/75/85 Hz)
		XGA 1024x768 (60/70/75/85 Hz)
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu/Select(Up,Down), Adjustment (+,-), Auto-tune
Plug & Play		DDC1/2B compatible
Power Adapter		Input AC 90~264V, 50~60Hz; Output DC 12V / 3.5A
Operating Conditions	Temperature	5°C-35°C (41°F-95°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)
	Humidity	10%-90% (no condensation)
Certification		C-UL, FCC, CE, MPR II, EPA, NUTEK, TCO (optional)

* Specifications are subject to change without notice.

Catch the wave of the future - Now!

Gvision USA Inc.

1582 Parkway Loop, Suite C, Tustin, CA 92780

