

# F5AX Series - 15" LCD Monitor/TV

## - Product Specifications -

Configuration		F5AX
LCD Display Area		15.0" TFT Active Matrix Panel
Display Size (HxV)		12"x9" (304x 228mm)
Pixel Pitch (HxV)		0.297x0.297mm
Max. Resolution		XGA 1024 x 768
Contrast Ratio		300 : 1 (typical)
Brightness		250 cd/m <sup>2</sup> (typical)
Response Time		30 ms (typical)
Display Color		16M
Viewing Angle	L/R	120°
	U/D	100°
Input Signal	Video	RGB Analog 0.7V <sub>p-p</sub>
	Sync	TTL Positive or Negative
Display Mode		VGA 640 x 350 (70 Hz)
		VGA 720 x 400 (70 Hz)
		VGA 640 x 480 (60/72/75 Hz)
		SVGA 800 x 600 (60/72/75 Hz)
		XGA 1024 x 768 (60/70/75 Hz)
Signal Connector	Analog	15 pin D-sub
	Digital	24 -pin DVI
Front Control		Power Switch, Menu/Select (up, down), Adjust (+, -)
Video-In (option)		S-video and RCA connector
Plug & Play		DDC 1/2B
Power Adapter		Input AC 100-240V, 50-60Hz, Output DC 12V/4.0A
Operating Conditions	Temperature	5°C ~ 35°C (41°F ~ 95°F)
	Humidity	20% ~ 80% (no condensation)
Storage Conditions	Altitude	To 10,000 Feet
	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
Audio System	Humidity	10% ~ 90% (no condensation)
	Speakers	1W / Per Channel
USB (option)	Connector	Earphone jack, Audio-out jack
		1 Upstream Port, 2 Downstream Ports
TV Tuner (option)		TV Tuner (PAL or NTSC), Remote Control
Card Reader/ JPEG Player (option)		CF, SD, MMC, SM Compatible
Dimensions (HxWxD)		13.4"x13.8"x6.4" (340x350x162mm)
Weight (Net)		6.8lbs. (3.1 Kgs)
Certifications		C-UL, FCC, TUV/GS, CE, EPA, NUTEK, BSMI, TCO99 (option)

Specifications are subject to change without notice.



20532 Crescent Bay Drive, Suite 104  
 Lake Forest, CA 92630  
 Tel: (949) 586-3338  
 Fax: (949) 586-3398

