

# F7AH Series - 17" LCD Monitor/TV

## - Product Specifications -

Configuration		F7AH
LCD Display Area		17.0" TFT Active Matrix Panel
Display Size (HxV)		13.3"x10.6" (337.9 x270.3mm)
Pixel Pitch (HxV)		0.264x0.264mm
Max. Resolution		SXGA 1280 x 1024
Contrast Ratio		350:1 (typical)
Brightness		300 cd/m2 (typical)
Response Time		30 ms (typical)
Display Color		16M
Viewing Angle	L/R	150°
	U/D	125°
Input Signal	Video	RGB Analog 0.7Vp-p
	Sync	TTL Positive or Negative
Display Mode		VGA 640 x 350 (70 Hz)
		VGA 720 x 400 (70 Hz)
		VGA 640 x 480 (60/72/75 Hz)
		SVGA 800 x 600 (60/72/75 Hz)
		XGA 1024 x 768 (60/70/75 Hz)
		SXGA 1280 x 1024 (60/75 Hz)
Signal Connector	Analog	15 pin D-sub
	Digital	24 -pin DVI
Video-In (option)		S-video and RCA connector
Front Control		Power Switch, Menu/Select (up, down), Adjust (+, -)
Plug & Play		DDC 1/2B
Power Adapter		Input AC 100-240V, 50-60Hz, Output DC 12V/4.0A
Operating Conditions	Temperature	5oC ~ 35oC (41oF ~ 95oF)
	Humidity	20% ~ 80% (no condensation)
Storage Conditions	Altitude	To 10,000 Feet
	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
Audio System	Humidity	10% ~ 90% (no condensation)
	Speakers	1W / Per Channel
USB (option)	Connector	Earphone jack, Audio-out jack
		1 Upstream Port, 2 Downstream Ports
TV Tuner (option)		TV Tuner (PAL or NTSC), Remote Control
Card Reader/ JPEG Player (option)		CF, SD, MMC, SM Compatible
Dimensions (HxWxD)		15.4"x15.5"x8" (390x392x202mm)
Weight (Net)		11.2lbs. (5.1 Kgs)
Certifications		C-UL, FCC, TUV/GS, CE, EPA, NUTEK, BSMI, TCO99 (option)

Specifications are subject to change without notice.



20532 Crescent Bay Drive, Suite 104  
 Lake Forest, CA 92630  
 Tel: (949) 586-3338  
 Fax: (949) 586-3398

