

J5NX

15" LCD Monitor With MSR

PRELIMINARY Product Specifications

SPECIFICATIONS		J5NX
LCD Display Area		15.0" TFT Active Matrix Panel
Display Size (HxV)		12"x9" (304x 228mm)
Pixel Pitch (HxV)		0.297x0.297mm
Max. Resolution		XGA 1024 x 768
Contrast Ratio		300 : 1 (typical)
Brightness		250 cd/m ² (typical)
Response Time		7 ms/ 23 ms (Tr/Tf)
Display Color		16M
Viewing Angle	L/R	120°
	U/D	+40°~-60°
Input Signal	Video	RGB Analog 0.7Vp-p
	Sync	TTL Positive or Negative
Display Mode		VGA 720 x 400 (70 Hz) VGA 640 x 480 (60/72/75 Hz) SVGA 800 x 600 (56/60/72/75 Hz) XGA 1024 x 768 (60/70/75 Hz)
Signal Connector	Analog	15 pin D-sub
	Digital	24 -pin DVI
Front Control		Power on/off with LED, Menu, Select(Up,Down), Adjustment(+/-)
Plug and Play		DDC 1/2B
Power		Input AC 100~240V, 50~60Hz; Output DC 12V / 3A
Operating Conditions	Temperature	41°F ~ 95°F (5°C ~ 35°C)
	Humidity	20% ~ 80% (no condensation)
	Altitude	To 10,000 Feet
Storage Conditions	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
	Humidity	10% ~ 90% (no condensation)
Audio System	Speakers	2W / Per Channel
	Connector	3.5mm Phone Jack
Video-In		S-Video and Composite Video (RCA Jack), Audio L/R
Dimensions (HxWxD)		TBD
Weight (Net)		TBD
Touch Options		Capacitive or Resistive (optional) with RS232 or USB Interface
Optional Module		Beige or black, tempered glass, pedestal stand, wall mount, pole mount
MSR Details		Two track MSR RS-232 Interface (optional)
Certifications		UL, C-UL, FCC-B, TUV, CE, BSMI

(Interface Options: 1. Video-In, tempered glass, 2. Touch panel, 3. Video-In and touch panel)
 Specifications are subject to change without notice.



Catch the wave of the future!

20532 Crescent Bay Dr. Suite 104
 Lake Forest, CA 92630
 Ph: 949-586-3338 Fax: 949-586-3398
 www.gvision-usa.com

