



# GVISION LCD Monitor: 15" Touchscreen Display

Configuration		J5PX - Product Specification -
LCD Display		15" TFT active matrix panel
Display Size (HxV mm)		304 x 228
Pixel Pitch (HxV mm)		0.297 x 0.297
Max. Resolution		XGA 1024x768
Bezel Color		<b>Beige or Black</b>
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m <sup>2</sup> (typical)
Response Time		25 ~ 30 ms
Display Color		16M
Viewing Angle	L/R	+70°~-70° (140° typical)
	U/D	+70°~-70° (140° typical)
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/66/70/72/75 Hz)
		SVGA 800x600 (60/70/72/75 Hz)
		<b>XGA 1024x768 (60/70/75 Hz)</b>
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu, Select, Adjustment (+,-)
OSD		Auto-tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall R.G.B. color drive, OSD format, Volume
Plug & Play		DDC1/2B compatible
Speaker		1W/per channel driver
Power		<b>Embedded AC input power system, universal 90-264 Volts</b>
Operating Conditions	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)		H: 13.5" x W: 15.25" x D: 3.0" (excluding base)
Weight (lbs)		11.4 (without base)
<b>Touch Screen Options</b>		<b>3M Resistive/Capacitive Touch Screen (USB or Serial Interface)</b>
		<b>ELO Resistive/Intellitouch-SAW (USB or Serial Interface)</b>
Certification		C-UL, FCC, TUV/GS, CE, MPR II, EPA, NUTEK, D, N, S, F, TCO (optional)

\* Specifications are subject to change without notice.



[www.gvision-usa.com](http://www.gvision-usa.com)

20532 Crescent Bay, Suite 104  
 Lake Forest, CA 92630  
 (949) 586-3338, (Ph)  
 (949) 586-3398 (Fax)